Bechikbaarheid filterzakken

Code	Material	Micron rating															Construction	Type of filtration	Media rating
		1	5	10	25	50	75	80	100	150	200	250	300	400	600	800			
PO	Polypropylene	•	•	•	•	•			•		•						sewn or welded	depth	nominal
POXL	Polypropylene extended life	•	•	•	•	•			•								sewn or welded	depth	nominal
POF	Polypropylene FDA	•	•	•	•												welded	depth	nominal
POXLF	Polypropylene extended life FDA	•	•	•													welded	depth	nominal
PE	Polyester	•	•	•	•	•			•		•						sewn or welded	depth	nominal
PEXL	Polyester extended life	•	•	•	•	•			•								sewn or welded	depth	nominal
PEF	Polyester FDA	•															welded	depth	nominal
PEXLF	Polyester extended life FDA	•	•	•													welded	depth	nominal
NY	Nylon		•	•	•	•			•								sewn	depth	nominal
HT	Nomex	•	•	•	•	•			•								sewn	depth	nominal
PT	PTFE	•	•	•													sewn	depth	nominal
NMO	Nylon monofilament		•	•	•	•		•	•	•	•	•	•	•	•	•	sewn	surface	absolute
PMO	Polypropylene monofilament								•	•	•		•	•	•	•	sewn	surface	absolute
PEMU	Polyester multifilament								•	•	•	•	•	•	•	•	sewn	surface	nominal
PEMO	Polyester monofilament					•		•		•	•			•			sewn	surface	absolute
PTMOPTFE	Monofilament								•	•	•	•		•	•		sewn	surface	absolute
AGF	Meltblown polypropylene	51, 53, 55, 57 (from 0,2µ to 10µ at >60% efficiency)															welded	depth	absolute
AGFE	Meltblown polyester	51, 55, 57 (from 0,2µ to 2µ at >60% efficiency)															welded	depth	absolute
PGF	Long life meltblown polypropylene	50, 51, 55, 57 (from 0,45µ to 20µ at >99% efficiency)															welded	depth	absolute